

Safety Data Sheet

Artline[®] Xstamper

(P303+P361+P353)

Issued Date: 16 May 2008 Revised Date: 22 March 2021

(MSDS)

		Revised Date : 22	March 2021
SECTION 1	CHEMICAL PRODUCT AND	COMPANY IDENTIFICATION	
Product Name	 Xstamper Refill Ink dyestuff typ XR-2N (X-200) (X-200 ink) XR-6N (X-200) XR-30S XR-100S Xstamper Products Dyestuff type Xstamper 		A Stamper
Company Name Address Telephone Fax Contact (e-mail) Emergency Call Recommended us	se : Stamp ink		
SECTION 2	HAZARDS IDENTIFICATION		
Hazardous to	ds quids Hazards the aquatic environment (acute) the aquatic environment (chronic) the ozone layer	Category 3 Category 2A Classification not possible Classification not possible Classification not possible	
Signal word	: Warning	Recommendations on the TRANSPORT OF DANGEROUS GOUNTED NATIONS. Refer to section 9 and 14.	JODS,
Hazard stateme	-		(H226) (H319)
Take precaut Wash hands Wear eye pro 【Response】 IF IN EYES	om heat, hot surfaces, sparks, open fl ionary measures against static discha thoroughly after handling.	al minutes.	(P210) (P243) (P264) (P280) (P305+P351+P338
	n persists : Get medical advice and att		(P337+P313)

IF ON SKIN (or hair) : Take off immediately all contaminated clothing. Rinse skin with water.

In case of fire : Use dry chemical powder, foam or carbon dioxide to extinguish.
[Storage]
Store in a well-ventilated place. Keep container tightly closed.
[Disposal]
Dispose of contents and container in accordance with local regulations.

(P370+P378)

(P403+P233)

(P501)

SECTION 3

COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Ingred	lients	
--------	--------	--

Chemical Name / Generic name	Composition weight %	CAS Registry No.	Hazard Class (category)	Hazard statement
Ethanol	1 ~ 10	64-17-5	Flam. Liq. 2	H225
Derivative of vegetable oil	45 ~ 55	Confidential	none	none
Glycol class solvent	5 ~ 15	Confidential	none	none
2-(2-Butoxyethoxy)ethanol	5 ~ 15	112-34-5	Eye Irrit. 2A	H319
Synthetic resin	5 ~ 15	Confidential	none	none
Dyestuff	10 ~ 20	Confidential	none	none
total	100			

SECTION 4 FIRST-AID MEASURES

IF INHALED	 Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.
IF ON SKIN	 Remove / Take off immediately all contaminated clothing. Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.
IF IN EYES	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.
IF SWALLOWED	: After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient when not conscious. Receive the doctor's treatment (stomach pump) promptly.

SECTION 5 FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA

: Dry chemical powder, foam or carbon dioxide

UNSUITABLE EXTINGUISHING MEDIA : Water jet

SPECIFIC EXTINCTION METHOD

For initial stage extinction, carbon dioxide or dry chemical powder.

When a fire extends, fire is extinguished by a large amount of water spray.

Do not discharge extinguishing waters into the aquatic environment.

SPECIAL PROTECTIVE FOR FIRE- FIGHTERS

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn. Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Evacuate personnel to safe area. Shut off all sources of ignition.

No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

ENVIRONMENTAL PRECAUTIONS

Do not throw the leakage thing directly into environment

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth, etc.), and then wipe off the waste well with waste cloth, and rag.

In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.)

and collect into empty container by scoop, suction equipment or the like.

SECONDARY ACCIDENT PREVENTION MEASURE

All ignition sources should be quickly removed. (No smoking in vicinity, prohibit sparks or fire sources.)

SECTION 7	HANDLING AND STC	RAGE
	e with adequate ventilation.	
-	bid contact with skin, eyes and	d clothing.
	tain special instructions before	
		cautions have been read and understood.
	not eat, drink or smoke when	
-		nd store in a cool and dry place.
	ep away from heat and flame, ep out of the reach of children	с с
SECTION 8		OLS AND PERSONAL PROTECTION
ACGIH (2020)	L EXPOSURE LIMIT	
Ethanol	STEL	1,000 ppm
	vethoxy)ethanol TWA	10 ppm
OSHA PEL		
Ethanol	TWA	1,000 ppm
DIRECTIVE 2	006/15/EC	
2-(2-Butoxy	vethoxy)ethanol TWA	10 ppm
Japan Society	for Occupational Health (202	0) Not listed
PERSONAL PR	OTECTION	
Respiratory F	rotection : Use with local e	xhaust ventilation, when in long use.
	Avoid breathing	vapours. Wear mask to prevent organic gas, if necessary.
Hand Protect	on : Avoid contact w	ith hands. Wear safety gloves, if necessary.
Eye Protectio	n : Avoid contact w	ith eyes. Wear safety glasses, if necessary.
Skin Protectio	on : Avoid skin conta	act. Wear personal protection apron, boots, if necessary.
SECTION 9	PHYSICAL AND CHE	MICAL PROPERTIES
Appearance	: Blue liquid	
Odour	: None	
рН	: Not applicable	
Boiling point	: 78 ~ 225 °C	
Flash point	: 40.0 °C (closed	cup) Not sustained combustibility : Refer to section14
Relative Density	/ (at 25°C) ∶ 1.0 (g/cm ³)	
Solubility in Wa	ter : Insoluble	
SECTION 10	STABILITY AND REA	CTIVITY
Stability	: St	able under normal handling.
Conditions to A	void : Hi	gh temperature, Direct sunlight, Fire
Incompatible Ma	aterials : St	rong oxidising agents
Hazardous Deco	omposition Products : Co	D, CO ₂
SECTION 11	TOXICOLOGICAL INI	FORMATION
Acute toxicity	: LD/LC50 values that are	relevant for classification
-	[Ethanol]	
		050 >5,000 mg/kg
	Inhalation-rat LC	C50 >20 mg/L/4h

Hererdeue te the equatic environment (equite)					
SECTION 12	ECOLOGICAL INF	ORMAT	ΓΙΟΝ		
Carcinogenicity	 This product does not contain any component that is considered a human carcinogen by IARC, ACGIH, EPA, EU or NTP. 				
Eye irritation	: Category 2A Cat	uses serio	us eye irritation		
	Dermal-rabbit	LD50	>2,000 - <=5,000 mg/kg		
	Oral-rat LD50 >2,000 - <=5,000 mg/kg				
	[2-(2-Butoxyethoxy)	ethanol]			
	Dermal-rabbit	LD50	>5,000 mg/kg		
	Oral-rat	LD50	>5,000 mg/kg		
	[Glycol class solven	t]			
[ISO11014:2009][Shachihata Inc.] [X-200_blue_i] 4/5					

nazardous to the aquatic environment (acute)	
Hazardous to the aquatic environment (chronic)	: Classification not possible
Hazardous to the ozone layer	: Classification not possible

Hazardous to the ozone layer

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal must be made according to official regulations.

Comply with all Federal, State, and Local regulations regarding disposal.

Do not allow product to reach ground, any water course or sewage system.

SECTION 14 TRANS	PORT INFORMATION	
UN number	(DOT, ADR, IMDG, IATA)	: None
UN proper shipping name	(DOT, ADR, IMDG, IATA)	: None
UN Classification		: None
Packing group	(DOT, ADR, IMDG, IATA)	: None
Marine pollutant (Y/N)		: N
EmS number		: None

This product has passed the SUSTAINED COMBUSTIBILITY TEST prescribed in the UN Manual of Tests and Criteria, Part III, subsection 32.5.2. Liquids with a flash point of more than 35 °C which do not sustain combustion need not be considered as flammable liquids. Refer to Recommendations on the TRANSPORT OF DANGEROUS GOODS, UNITED NATIONS - Seventeenth revised edition (ST/SG/AC.10/1/Rev.17) CHAPTER 2.3 CLASS 3 - FLAMMABLE LIQUIDS (see 2.3.1.2 and 2.3.1.3), IATA Dangerous Goods Regulations Section 3.3.1.3 and IMDG Code Section 2.3.1.3.

REGULATORY INFORMATION SECTION 15

< EU Information > Regulation (EC) No 1272/200 Substance name Hazard Class & Category Symbols Signal word Hazard statements	 [Ethanol] Flammable liquids, Category 2 GHS02 Danger 	ıd vapour	
Substance name Hazard Class & Category Symbols Signal word Hazard statements	: GHS07 : Warning	on	
< USA Information > OSHA STATUS : This product is hazardous under 29 CFR 1910.1200. TSCA STATUS : All components on TSCA INVENTORY. TSCA Hazard Communication Program (40 CFR Part 721) (SNUR) : Not Applicable CERCLA REPORTABLE QUANTITY (40 CFR 117,302) : Not Applicable SARA TITLE III Section 313 (40 CFR 372) : Listed (2-(2-Butoxyethoxy)ethanol) California Proposition 65 : Not listed			

Refer to any other federal, state, EU, national and local regulations.

SECTION 16 OTHER INFORMATION



This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.

EU RoHS(Directive 2011/65/EU)EU ELV(DIRECTIVE 2000/53/EC)