

Artline & Xstamper

(P271)

(P264)

Safety Data Sheet (M

(MSDS)

Issued Date : 27 July, 2021 Revised Date : 12 March, 2025

		Revised Date : 12 March, 2	2025
SECTION 1	CHEMICAL PRODUCT AND (COMPANY IDENTIFICATION	
Product Name	: TAT INDELIBLE INK Multip STGA Red STGA-1-R (Small bottle), STGA	Colou	r
	TAT INDELIBLE STAMP PA ATGA-2, ATGA-3, ATGA- ATGA-2-R (Medium), ATGA-3-F		
Company Name Address Telephone Fax Contact Emergency Call Recommended us	 + 81- 52- 521- 3600 + 81- 52- 521- 3899 <u>https://www.artlineworld.com/</u> + 81- 52- 521- 3600 (Sha Stamp ink 	u, Nagoya City, 451-0021, Japan <u>/contact/</u> chihata Inc. [Japan])	
SECTION 2	HAZARDS IDENTIFICATION		
GHS Classification Physical Hazard Flammable liq Health Hazards Specific targe Environmental	s uids organ toxicity ; single exposure	Category 3 Category 3 (respiratory tract irritation, narcotic	effects)
Hazardous to	he aquatic environment (chronic)	Classification not possible Classification not possible Classification not possible	
LABEL ELEMENTS Symbols			
Signal word	: Warning		
Hazard stateme	nt : Flammable liquid and vapo May cause respiratory irrita May cause drowsiness or d	tion	(H226) (H335) (H336)
	om heat, hot surfaces, sparks, oper o prevent static discharges. tection.	n flames and other ignition sources. No smoking.	(P210) (P243) (P280) (P281)

Use only outdoors or in a well-ventilated area.

Wash hands thoroughly after handling.

SECTION 3	COMPOSITION/INFORMATION ON INGREDIENTS	
Dispose o	of contents and container in accordance with local regulations.	(P501)
【Disposa	1	
Store in a	well-ventilated place. Keep container tightly closed.	(P403+P233)
[Storage		
IF SWAL	_OWED : Get medical advice if you feel unwell. Rinse mouth.	(P301+P314+P330)
lf skin irri	ation occurs : Get medical advice and attention.	(P332+P313)
	Rinse skin with water [orshower].	
IF ON SH	(IN (or hair) : Take off immediately all contaminated clothing.	(P303+P361+P353)
Call a PC	ISON CENTER or physician if you feel unwell.	(P312)
IF INHAL	ED : Remove person to fresh air and keep comfortable for breathing.	(P304+P340)
In case o	fire : Use dry chemical powder, foam or carbon dioxide to extinguish.	(P370+P378)
[Respons	se]	

Substance / Mixture : Mixture Ingredients :

Chemical Name /	Composition	CAS	Hazard Class	Hazard statement
Generic name	weight %	Registry No.	(category)	
1-Methoxypropan-2-ol	15 ~ 25	107-98-2	Flam. Liq. 3 STOT. SE. 3	H226 H336
(2-Methoxymethylethoxy)propanol	55 ~ 65	34590-94-8	Flam. Liq. 4 STOT. SE. 3	H227 H335

SECTION 4	FIRST-AID MEASURES
IF INHALED	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a doctor if symptoms persist.
IF ON SKIN	Remove / Take off immediately all contaminated clothing. Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.
IF IN EYES	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.
IF SWALLOWED	After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient when not conscious. Receive the doctor's treatment (stomach pump) promptly.

SECTION 5 FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA : Dry chemical powder, foam or carbon dioxide

UNSUITABLE EXTINGUISHING MEDIA : Water jet

SPECIFIC EXTINCTION METHOD

For initial stage extinction, carbon dioxide or dry chemical powder.

When a fire extends, fire is extinguished by a large amount of water spray.

Do not discharge extinguishing waters into the aquatic environment.

SPECIAL PROTECTIVE FOR FIRE- FIGHTERS

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn. Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathi apparatus and other protective equipment.

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Evacuate personnel to safe area. Shut off all sources of ignition.

No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

[ISO11014:2009][Shachihata Inc.] [STGA_red_d] 3/5

ENVIRONMENTAL PRECAUTIONS

Do not throw the leakage thing directly into environment.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth, etc.), and then wipe off the waste well with waste cloth, and rag.

In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.)

and collect into empty container by scoop, suction equipment or the like.

SECONDARY ACCIDENT PREVENTION MEASURE

All ignition sources should be quickly removed. (No smoking in vicinity, prohibit sparks or fire sources.)

SECTION 7 HANDLING AND STORAGE

 Handling : Use with adequate ventilation. Avoid contact with skin, eyes and clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product.

Storage: Keep containers tightly closed and store in a cool and dry place.
Keep away from heat and flame, ignition source and sunlight.
Keep out of the reach of children.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMIT

ACGIH (2024)		
1-Methoxypropan-2-ol	TWA	50 ppm
(2-Methoxymethylethoxy)propanol	TWA	50 ppm
OSHA PEL		
(2-Methoxymethylethoxy)propanol	TWA	100 ppm
DIRECTIVE 2000/39/EC		
1-Methoxypropan-2-ol	TWA	100 ppm
(2-Methoxymethylethoxy)propanol	TWA	50 ppm

Japan Society for Occupational Health (2024)

PERSONAL PROTECTION

Respiratory Protection	:	Use with local exhaust ventilation, when in long use.
		Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.
Hand Protection	:	Avoid contact with hands. Wear safety gloves, if necessary.
Eye Protection	:	Avoid contact with eyes. Wear safety glasses, if necessary.
Skin Protection	:	Avoid skin contact. Wear personal protection apron, boots, if necessary.

Not listed

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Red liquid
Odour	: Minor solvent odour
рН	: Not applicable
Boiling point	∶ 117 ~ 189 ℃
Flash point	$\stackrel{:}{_{\sim}}$ 50 $^{\circ}\!\mathrm{C}$ (closed cup)
Relative Density	∶ 0.95 ~ 1.05 g/cm ³ (25℃)
Solubility in Water	: Insoluble

SECTION 10 STABILITY AND REACTIVITY

Stability	Stable under normal handling.
Conditions to Avoid	: High temperature, Direct sunlight, Fire
Incompatible Materials	Strong oxidising agents
Hazardous Decomposition Products	: CO, CO ₂

SECTION 11	TOXICOLOGICAL INFORMATION
Acute toxicity	: LD/LC50 values that are relevant for classification
	[1-Methoxypropan-2-ol]
	Oral-rat LD50 >2,000 - <=5,000 mg/kg
	Dermal-rabbit LD50 >5,000 mg/kg
	Inhalation-rat LC50 >20 mg/L/4h
	[(2-Methoxymethylethoxy)propanol]
	Oral-rat LD50 >5,000 mg/kg
	Dermal-rabbit LD50 >5,000 mg/kg
Specific target orga (single exposure)	
Carcinogenicity	This product does not contain any component that is considered a human carcinogen by IARC, ACGIH, EPA, EU or NTP.

SECTION 12 ECOLOGICAL INFORMATION

Hazardous to the aquatic environment (acute)	Classification not possible
Hazardous to the aquatic environment (chronic)	Classification not possible
Hazardous to the ozone layer	Classification not possible

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal must be made according to official regulations. Comply with all Federal, State, and Local regulations regarding disposal. **Do not allow product to reach ground, any water course or sewage system.**

SECTION 14 TRAN	ISPORT INFORMATION		
UN number	(DOT, ADR, IMDG, IATA)	: UN1993	
UN proper shipping name	(DOT, ADR, IMDG, IATA)	 FLAMMABLE LIQUID, N.O.S. (1-Methoxypropan-2-ol) 	
UN Classification		: 3	3
Packing group	(DOT, ADR, IMDG, IATA)	: 111	
Marine pollutant (Y/N)		: N	
EmS number		: F-E, S-E	

SECTION 15 REGULATORY INFORMATION

< EU Information >

Regulation (EC) No 1272/2008	3 (0	CLP)
Substance name	:	[1-Methoxypropan-2-ol]
Hazard Class & Category	:	Flammable liquids, Category 3
		Specific target organ toxicity - single exposure, Category 3
Symbols	:	GHS02, GHS07
Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour
		H336 May cause drowsiness or dizziness

< USA Information >

OSHA STATUS : This product is hazardous under 29 CFR 1910.1200.	
: Not Applicable	
: Not Applicable	
: Not Applicable	

[ISO11014:2009] [Shachihata Inc.] [STGA_red_d] 5/5

California Proposition 65

: Not listed

Refer to any other federal, state, EU, national and local regulations.

SECTION 16 OTHER INFORMATION



This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.

EU RoHS(Directive 2011/65/EU)EU ELV(DIRECTIVE 2000/53/EC)