

# **Artline**

# **Xstamper**

# Safety Data Sheet (MSDS)

Issued Date: Nov. 4th, 2015

Artline SUPREME

Artline SUPREME

**SECTION 1** CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Name** : Artline Supreme Permanent Marker Colour: (Royal blue)

**EPF-700** 

**Company Name** : Shachihata Inc.

**Address** : 4-69, Amazuka-cho, Nishi-ku, Nagoya City, 451-0021, Japan

Telephone : +81-52-521-3600 : +81-52-521-3899 Fax

: chem-analysis@ngy.shachihata.co.jp Contact (e-mail)

**Emergency Call** : +81-52-521-3600 (Shachihata Inc. [Japan])

Recommended use : Permanent marker ink

#### HAZARDS IDENTIFICATION **SECTION 2**

#### **GHS Classification**

**Physical Hazards** 

Flammable liquids Category 2

**Health Hazards** 

Serious eye damage Category 1

**Environmental Hazards** 

Hazardous to the aquatic environment (acute) Classification not possible Hazardous to the aquatic environment (chronic) Classification not possible Hazardous to the ozone layer Classification not possible



**Symbols** 





Signal word : Danger

: Highly flammable liquid and vapour **Hazard statement** (H225)

> Causes serious eye damage (H318)

Precautionary statement

[Prevention]

Keep out of reach of children. (P102)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharge. (P243)

Wear eye protection.

[Response]

In case of fire: Use dry chemical powder, foam or carbon dioxide to extinguish.

IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice and attention.

Immediately call a POISON CENTER or physician.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

If skin irritation occurs: Get medical advice and attention.

[Storage]

Store in a well-ventilated place. Keep container tightly closed.

Revised Date: Apr. 19th, 2019



(P210)

(P280)

(P370+P378)

(P337+P313)

(P332+P313)

(P403+P233)

(P310)

(P305+P351+P338)

(P303+P361+P353)

Dispose of contents and container in accordance with local regulations.

(P501)

### SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Ingredients :

Chemical Name / Generic name	Composition weight %	CAS Registry No.	Hazard Class (category)	Hazard statement
Ethanol	50 ~ 60	64-17-5	Flam. Liq. 2	H225
Propan-1-ol	5 ~ 15	71-23-8	Flam. Liq. 2 Eye Dam. 1 STOT. SE. 3	H225 H318 H336
Ethyl lactate	10 ~ 20	97-64-3	Flam. Liq. 3 Eye Dam. 1 STOT. SE. 3	H226 H318 H335
Benzyl alcohol	1 ~ 5	100-51-6	Acute Tox.(oral) 4 Acute Tox.(inhal.) 4 Eye Irrit. 2A	H302 H332 H319
Synthetic resin	5 ~ 15	Confidential	none	none
Dyestuff	5 ~ 10	Confidential	none	none
total	100			

### SECTION 4 FIRST-AID MEASURES

**IF INHALED** : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Consult a doctor if symptoms persist.

**IF ON SKIN** : Remove/Take off immediately all contaminated clothing. Wash with soap and water.

If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.

IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

**IF SWALLOWED**: After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach,

and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient

when not conscious. Receive the doctor's treatment (stomach pump) promptly.

### SECTION 5 FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA : Dry chemical powder, foam or carbon dioxide

**UNSUITABLE EXTINGUISHING MEDIA** : Water jet

SPECIFIC EXTINCTION METHOD

For initial stage extinction, carbon dioxide or dry chemical powder.

When a fire extends, fire is extinguished by a large amount of water spray.

Do not discharge extinguishing waters into the aquatic environment.

#### SPECIAL PROTECTIVE FOR FIRE- FIGHTERS

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn.

Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

### SECTION 6 ACCIDENTAL RELEASE MEASURES

# PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Evacuate personnel to safe area. Shut off all sources of ignition.

No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

#### **ENVIRONMENTAL PRECAUTIONS**

Do not throw the leakage thing directly into environment

#### METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth, etc.),

and then wipe off the waste well with waste cloth, and rag.

In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.)

and collect into empty container by scoop, suction equipment or the like.

#### SECONDARY ACCIDENT PREVENTION MEASURE

All ignition sources should be quickly removed. (No smoking in vicinity, prohibit sparks or fire sources.)

# SECTION 7 HANDLING AND STORAGE

**Handling**: Use with adequate ventilation.

Avoid contact with skin, eyes and clothing. Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not eat, drink or smoke when using this product.

**Storage** : Keep containers tightly closed and store in a cool and dry place.

Keep away from heat and flame, ignition source and sunlight.

Keep out of the reach of children.

## SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **OCCUPATIONAL EXPOSURE LIMIT**

ACGIH (2018)

Ethanol STEL 1,000 ppm Propan-1-ol TWA 100 ppm

OSHA PEL

Ethanol TWA 1,000 ppm Propan-1-ol TWA 200 ppm

DIRECTIVE 2000/39/EC none

Japan Society for Occupational Health (2018) none

#### PERSONAL PROTECTION

Respiratory Protection : Use with local exhaust ventilation, when in long use.

Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.

Hand Protection : Avoid contact with hands. Wear safety gloves, if necessary. Eye Protection : Avoid contact with eyes. Wear safety glasses, if necessary.

Skin Protection : Avoid skin contact. Wear personal protection apron, boots, if necessary.

### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance : royal blue liquid

Odour : minor solvent odour

pH : Not applicableBoiling point : 78 ~ 205°C

Flash point : 16.5°C (closed cup)

Relative Density (at 25°C) :  $0.85 \sim 0.95$  (g/cm<sup>3</sup>)

Solubility in Water : Insoluble

# SECTION 10 STABILITY AND REACTIVITY

**Stability** : Stable under normal handling.

Conditions to Avoid : High temperature, Direct sunlight, Fire

Incompatible Materials : Strong oxidising agents

Hazardous Decomposition Products : CO, CO<sub>2</sub>

# SECTION 11 TOXICOLOGICAL INFORMATION

**Acute toxicity** : LD/LC50 values that are relevant for classification

[Ethanol]

Oral-rat LD50 >5,000 mg/kg Inhalation-rat LC50 >20 mg/L/4h

[Propan-1-ol]

Oral-rat LD50 >2,000 mg/kg
Dermal-rabbit LD50 >2,000 mg/kg
Inhalation-rat LC50 >20 mg/L/4h

[Ethyl lactate]

Oral-rat LD50 >2,000 mg/kg
Dermal-rabbit LD50 >5,000 mg/kg

[Benzyl alcohol]

Oral-rat LD50 >300 - <=2,000 mg/kgInhalation-rat LC50 >10 - <=20 mg/L/4h

Serious eye damage : Category 1 Causes serious eye damage

Carcinogenicity : This product does not contain any component that is considered

a human carcinogen by IARC, ACGIH, EPA, EU or NTP.

# SECTION 12 ECOLOGICAL INFORMATION

Hazardous to the aquatic environment (acute) : Classification not possible

Hazardous to the aquatic environment (chronic) : Classification not possible

Hazardous to the ozone layer : Classification not possible

### SECTION 13 DISPOSAL CONSIDERATIONS

Disposal must be made according to official regulations.

Comply with all Federal, State, and Local regulations regarding disposal.

Do not allow product to reach ground, any water course or sewage system.

### SECTION 14 TRANSPORT INFORMATION

**UN number** (DOT, ADR, IMDG, IATA) : UN1210

UN proper shipping name (DOT, ADR, IMDG, IATA) : PRINTING INK, flammable

**EmS number** : F-E,S-D

☆☆

Artline Supreme Permanent Marker (EPF-700) is not a hazardous material by the special provision.

Artline Supreme Permanent Marker (EPF-700) (The amount of ink : less than 10ml)

UN number : UN3175

UN proper shipping name : Solids containing Flammable Liquid. n.o.s.

IATA Special Provision A46
IMDG Code Special Provision 216
ADG Special Provision 216

According to IATA Special Provision A46, and IMDG Code Special Provision 216, small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to as a hazardous material/dangerous goods provided there is no free liquid in the packet or article.



#### SECTION 15 REGULATORY INFORMATION

#### < EU Information >

Regulation (EC) No 1272/2008 (CLP)

Substance name : [Ethanol]

Hazard Class & Category : Flammable liquids, Category 2

Symbols : GHS02 Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour

Substance name : [Propan-1-ol]

Hazard Class & Category : Flammable liquids, Category 2

Serious eye damage, Category 1

Specific target organ toxicity - single exposure, Category 3

Symbols : GHS02,GHS07,GHS05

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour

H318 Causes serious eye damage

H336 May cause drowsiness or dizziness

Substance name : [Ethyl lactate]

Hazard Class & Category : Flammable liquids, Category 3

Serious eye damage, Category 1

Specific target organ toxicity - single exposure, Category 3

Symbols : GHS02,GHS07,GHS05

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour

H318 Causes serious eye damageH335 May cause respiratory irritation

Substance name : [Benzyl alcohol]

Hazard Class & Category : Acute toxicity (inhalation: vapour), Category 4

Acute toxicity (oral), Category 4

Symbols : GHS07 Signal word : Warning

Hazard statements : H332 Harmful if inhaled

H302 Harmful if swallowed

#### < USA Information >

OSHA STATUS: This product is hazardous under 29 CFR 1910.1200.

TSCA STATUS: All components on TSCA INVENTORY.

TSCA Hazard Communication Program (40 CFR Part 721) (SNUR) : Not Applicable CERCLA REPORTABLE QUANTITY (40 CFR 117,302) : Not Applicable SARA TITLE 

Section 313 (40 CFR 372) : Not Applicable California Proposition 65 : Not listed

Refer to any other federal, state, EU, national and local regulations.

# SECTION 16 OTHER INFORMATION



This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.