

Safety Data Sheet (MSDS)



Issued Date : Jul. 10th, 2009 Revised Date : Jan. 31st, 2019

SECTION 1	CHEMICAL PRODUCT AND CO	MPANY IDENTIFICATION	
Product Name	: Artline KAWAKIMA PEN permane K-177N,K-199N Artline KAWAKIMA PEN marking KR-ND	Artimulation Artimulation	
Company Name Address Telephone Fax Contact (e-mail) Emergency Call Recommended use		Cap can be left off	
SECTION 2 F	HAZARDS IDENTIFICATION		
GHS Classification Physical Hazards Flammab		Category 3	補充インキ Mts: 2000 油性でかー #// KIMO
	ye damage arget organ toxicity ; single exposure	Category 1 Category 3 (narcotic effects)	
Hazardou	is to the aquatic environment (acute) is to the aquatic environment (chronic) is to the ozone layer	Classification not possible Classification not possible Classification not possible	● が 替 一 一 一 一 一 一 一 一 一 一 一 一 一
Signal word	: Danger	\mathbf{v}	
Hazard statemen	-	ess	(H226) (H318) (H336)
Precautionary st	-		
Keep out of rea Keep away fror Take precautio Avoid breathing	n heat, hot surfaces, sparks, open flam nary measures against static discharge g vapours. ors or in a well-ventilated area.	es and other ignition sources. No smoking.	(P102) (P210) (P243) (P261) (P271) (P280)
	Use dry chemical powder, foam or carb	oon dioxide to extinguish.	(P370+P378

(P304+P340) (P305+P351+P338)

IF INHALED : Remove person to fresh air and keep comfortable for breathing. IF IN EYES : Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.	
If eye irritation persists : Get medical advice and attention.	(P337+P313)
Immediately call a POISON CENTER or physician.	(P310)
IF ON SKIN (or hair) : Take off immediately all contaminated clothing. Rinse skin with water.	(P303+P361+P353)
If skin irritation occurs : Get medical advice and attention.	(P332+P313)
[Storage]	
Store in a well-ventilated place. Keep container tightly closed.	(P403+P233)
[Disposal]	
Dispose of contents and container in accordance with local regulations.	(P501)
-	

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture Ingredients :

Chemical Name / Generic name	Composition weight %	CAS Registry No.	Hazard Class (category)	Hazard statement
Propan-1-ol	80 ~ 90	71-23-8	Flam. Liq. 2 Eye Dam. 1 STOT. SE. 3	H225 H318 H336
Synthetic resin	5 ~ 15	Confidential	none	none
Dyestuff	1 ~ 5	Confidential	none	none
Additive	1 ~ 5	Confidential	none	none
total	100			

SECTION 4 FIRST-AID MEASURES

IF INHALED	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	Consult a doctor if symptoms persist.

- **IF ON SKIN** : Remove / Take off immediately all contaminated clothing. Wash with soap and water. If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.
- **IF IN EYES** : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.
- **IF SWALLOWED** : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach, and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient when not conscious. Receive the doctor's treatment (stomach pump) promptly.

SECTION 5 FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA : Dry chemical powder, foam or carbon dioxide

: Water jet

UNSUITABLE EXTINGUISHING MEDIA

SPECIFIC EXTINCTION METHOD

For initial stage extinction, carbon dioxide or dry chemical powder.

When a fire extends, fire is extinguished by a large amount of water spray.

Do not discharge extinguishing waters into the aquatic environment.

SPECIAL PROTECTIVE FOR FIRE- FIGHTERS

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn. Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Evacuate personnel to safe area. Shut off all sources of ignition.

No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

ENVIRONMENTAL PRECAUTIONS

Do not throw the leakage thing directly into environment

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

[ISO11014:2009] [Shachihata Inc.] [KR-ND_blue_i] 3/5

In case of a small spill, remove by absorbing with absorbents (sawdust, soil, sand, waste cloth, etc.), and then wipe off the waste well with waste cloth, and rag.

In case of large spills, prevent leakage by enclosing with nonflammables (earth and sand, etc.)

and collect into empty container by scoop, suction equipment or the like.

SECONDARY ACCIDENT PREVENTION MEASURE

All ignition sources should be quickly removed. (No smoking in vicinity, prohibit sparks or fire sources.)

SECTION 7 HANDLING AND STORAGE

Handling : Use with adequate ventilation. Avoid contact with skin, eyes and clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product.

Storage: Keep containers tightly closed and store in a cool and dry place.
Keep away from heat and flame, ignition source and sunlight.
Keep out of the reach of children.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMIT

TWA	100 ppm
TWA	200 ppm
none	
	TWA

Japan Society for Occupational Health (2018) none

PERSONAL PROTECTION

Respiratory Protection	:	Use with local exhaust ventilation, when in long use.
		Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.
Hand Protection	:	Avoid contact with hands. Wear safety gloves, if necessary.
Eye Protection	:	Avoid contact with eyes. Wear safety glasses, if necessary.
Skin Protection	:	Avoid skin contact. Wear personal protection apron, boots, if necessary.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: blue liquid
Odour	: minor solvent odour
рН	: Not applicable
Boiling point	: 97°C
Flash point	:25°C (closed cup)
Relative Density (at 25°C)	[:] 0.8 ~ 0.9 (g/cm ³)
Solubility in Water	: Insoluble

SECTION 10 STABILITY AND REACTIVITY

Stability	: Stable under normal handling.
Conditions to Avoid	: High temperature, Direct sunlight, Fire
Incompatible Materials	: Strong oxidising agents
Hazardous Decomposition Products	: CO, CO ₂

SECTION 11 TOXICOLOGICAL INFORMATION

Acute toxicity

 LD/LC50 values that are relevant for classification [Propan-1-ol]

LD50

>2,000 mg/kg

Oral-rat

	Dermal-rabb Inhalation-ra		>2,000 mg/kg >20 mg/L/4h
Serious eye damage	: Category 1	Causes serious	s eye damage
Specific target organ toxicity (single exposure)	Category 3	May cause dro	wsiness or dizziness
Carcinogenicity	This product does not contain any component that is considered a human carcinogen by IARC, ACGIH, EPA, EU or NTP.		

SECTION 12 ECOLOGICAL INFORMATION

Hazardous to the aquatic environment (acute)	Classification not possible
Hazardous to the aquatic environment (chronic)	: Classification not possible
Hazardous to the ozone layer	: Classification not possible

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal must be made according to official regulations.

Comply with all Federal, State, and Local regulations regarding disposal.

Do not allow product to reach ground, any water course or sewage system.

SECTION 14 TRANSPORT INFORMATION

UN number	(DOT, ADR, IMDG, IATA)	: UN1210	
UN proper shipping name	(DOT, ADR, IMDG, IATA)	: PRINTING INK, flammable	
UN Classification		: 3	
Packing group	(DOT, ADR, IMDG, IATA)	: 11	3
Marine pollutant (Y/N)		: N	
EmS number		: F-E,S-D	

☆☆

Artline KAWAKIMA PEN (K-177N,K-199N) is not a hazardous material by the special provision.

Artline KAWAKIMA PEN (K-177N,K-199N)		(The amount of ink : less than 10ml)
UN number	: UN3175	
UN proper shipping name	: Solids containing Flammable	e Liquid. n.o.s.
IATA	Special Provision A46	
IMDG Code	Special Provision 216	

According to IATA Special Provision A46, and IMDG Code Special Provision 216, small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group I or II absorbed onto a solid material are not subject to as a hazardous material/dangerous goods provided there is no free liquid in the packet or article.

SECTION 15 REGULATORY INFORMATION

< EU Information >

Regulation (EC) No 1272/2008 (CLP)

Substance name	: [Propan-1-ol]
Hazard Class & Category	: Flammable liquids, Category 2
	Serious eye damage, Category 1
	Specific target organ toxicity - single exposure, Category 3
Symbols	: GHS02,GHS07,GHS05
Signal word	: Danger
Hazard statements	: H225 Highly flammable liquid and vapour
	H318 Causes serious eye damage
	H336 May cause drowsiness or dizziness

< USA Information >

OSHA STATUS : This product is hazardous under 29 CFR 1910.1200. TSCA STATUS : All components on TSCA INVENTORY.

TSCA Hazard Communication Program (40 CFR Part 721) (SNUR)

CERCLA REPORTABLE QUANTITY (40 CFR 117,302)

SARA TITLE III Section 313 (40 CFR 372)

California Proposition 65

- : Not Applicable
- : Not Applicable
- : Not Applicable
 - : Not listed

Refer to any other federal, state, EU, national and local regulations.

SECTION 16 OTHER INFORMATION



This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that is described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information, there is no guarantee for the accuracy of the content.

EU RoHS Directive(2011/65/EC) ELV Directive(2000/53/EC)